



FIXED



Referencia <i>Reference</i>	Pot. Total <i>Total Power</i>	Regulación * <i>Dimmer *</i>	Ángulo < <i>Angle <</i>	Voltaje <i>Voltage</i>	Color # <i>Colour #</i>	Lúmenes <i>Lumens</i>	Ø Corte <i>Ø Cutting</i>	Medidas DxL <i>Measures DxL</i>		
110101*<5#	10W	0 = Non Dimm. D = DIM 1-10 L = DALI T = TRIAC	0 = 15° X = 24° Y = 36°	220~240 VAC	H = 2700K 2 = 3000K 0 = 4000K 1 = 5000K	1000lm	85mm	95x125mm		
110102*<5#	15W					1500lm	85mm	95x125mm		
110103*<5#	15W					1500lm	120mm	130x166mm		
110104*<5#	20W					2000lm	120mm	130x166mm		
110105*<5#	30W		W = 20° X = 24° 1 = 30° Y = 36° 2 = 45°			3000lm	120mm	130x145mm		
110106*<5#	15W					1500lm	150mm	160x165mm		
110107*<5#	20W					2000lm	150mm	160x165mm		
110108*<5#	25W					2500lm	150mm	160x165mm		
110109*<5#	30W					3000lm	170mm	180x180mm		
110110*<5#	40W					4000lm	170mm	180x180mm		



Descripción / Description:

Downlight empotrable con tecnología LED de alta potencia y alto brillo con diseño de doble reflector y multiples aplicaciones de iluminación. Incorpora un disipador de calor hecho en aluminio a presión que conduce el calor del chip eficazmente, proporcionando un rendimiento eficaz y una larga vida útil. Equipa un reflector especialmente diseñado con una tecnología de reflejo para evitar un reflejo secundario y deslumbramiento consiguiendo una distribución precisa de la luz. Instalación y mantenimiento sin necesidad de herramientas. CRI: >82 Opcional CRI: >92 Opcional: Regulable EEI: A++ L80 B10 3 MACADAM 50.000 H Garantía: 5 años

Recessed downlight with high power and high brightness LED technology with double reflector design with multiple lighting applications. It incorporates a heat sink made of aluminum under pressure that effectively conducts the heat of the chip, providing an efficient performance and a long service life. It equips a reflector specially designed with a reflex technology to avoid a secondary reflection and glare obtaining an accurate distribution of the light.

Installation and maintenance without tools.


CRI: >82
Optional CRI: >92
Optional: Dimmable
EEI: A++
L80 B10
3 MACADAM
50,000 H
Warranty: 5 years

Materiales / Materials

Cuerpo de aluminio inyectado.
Pintura electrostática en polvo.
Difusor de policarbonato.

Die cast aluminum body.
Electrostatic powder paint.
Polycarbonate diffuser.

Características técnicas / Technical features:



Certificados / Quality certificates:




Aplicaciones / Applications:



FIXED

Datos fotométricos / Photometrical data:



Instalación / Installation:

Empotrable / Recessed